



Modalix DevKit



Overview

The SiMa.ai MLSoC Modalix™ Development Kit (DevKit) is a complete hardware and software platform for evaluating and prototyping intelligent Physical AI applications using the latest MLSoC Modalix System-on-Module (SoM).

Designed for rapid deployment, this kit enables seamless development, benchmarking, and proof-of-concept creation with SiMa.ai's Palette™ software, offering best-in-class performance-per-watt in a compact form factor. Ideal for industrial, robotics, and vision-based and LLM-based applications, this kit supports real-time inferencing across computer vision, transformer models, and GenAI workloads.

Development Flow

Evaluate. Prototype. Demonstrate.

Evaluate

Use Palette to compile and run models, assess performance (FPS, latency, compute utilization), and monitor system metrics.

The kit provides:

- Docker-based toolchain
- ARM cross-compiler
- Platform image build & deploy tools
- Integrated KPIs and performance feedback

Prototype

Developers can rapidly prototype functional pipelines using SiMa.ai's Python APIs, enabling fast bring-up of custom ML workflows directly on the hardware without complex embedded optimization.

Demonstrate

The DevKit supports multi-camera input via MIPI CSI-2, IP, and high-speed USB 3.2, allowing developers to demonstrate real-time vision AI applications via an HDMI display with minimal latency.

Powered by MLSoC Modalix SoM

The MLSoC Modalix SoM combines the power and performance of Modalix with extended peripherals, all in a compact form factor designed to scale Physical AI deployments. Built on the field-proven MLSoC, Modalix, with its rich peripherals and unique architecture, delivers exceptional performance for multimodal Transformers, LLMs, LMMs, and GenAI workloads, while also supporting legacy CNN and computer vision algorithms.

The Modalix SoM offers the best-in-class performance per watt.

What's Included

- DevKit with enclosure (Modalix SoM and Carrier Board)
- Universal power adaptor (DC 12V @ 5A)
- M.2 500GB NVME storage

Universal power adaptor
(DC 12V @ 5A)




M.2 500GB SSD



Available Interfaces

- HDMI 1.4 @ 4K
- 2 x MIPI CSI-2 Connectors
- M.2 M 4x PCIe Gen4 RC/EP,
- 4x USB 3.2
- 1x USB-C
- 1x Gigabit Ethernet
- I2C/UART/GPIO/SPI/GPIO



Subsystem	Specifications
MLSoC Modalix with ML Accelerator (MLA)	50 TOPs (BF16, INT8, INT16); supports GenAI and neural networks
Application Processor	8x Arm Cortex-A65 @1.4–1.5 GHz; 32k Dhrystone MIPS
Memory	32 GB 128-bit LPDDR5, 128-bit @ 6400 Mbps
Video Codec	H.264/H.265/AV1 Decode 4K@60; H.264/H.265 Encode 4K@60
Computer Vision (CVU)	4-core Synopsys EV74 @ 1 GHz; 720 16-bit GOPS
Image Signal Processor	ARM Mali-C71 @ 1.2 GHz; supports RAW up to 24-bit, RGGB, RCCG, RCCB, RGBIR, WDR
Storage	16GB eMMC, 64MB QSPI, 128Kb EEPROM
Advanced Security	Secure boot, encryption, key storage, user code API
Operating Temperature Range	0-35°C

Ordering Information

Product Name Description
Modalix DevKit 32GBwith HDMI

Temperature Grade
Commercial & Industrial

Note: The Modalix DevKit provides limited PCIe (Gen4 only) and Ethernet (1G only) functionality due to the limitations of the Carrier board capabilities.



About SiMa

SiMa.ai is a leader in Physical AI, delivering a purpose-built, software-centric platform that brings best-in-class performance, power efficiency, and ease of use to Physical AI applications. Focused on scaling Physical AI across robotics, automotive, industrial automation, aerospace & defense, smart vision, and healthcare, SiMa.ai is led by seasoned technologists and backed by top-tier investors. Headquartered in San Jose, California. Learn more at www.sima.ai.

